

ECTAL 03/00/54
18 SEP 2003

REC'D 08 OCT 2003

WIPO PCT

PA 991152

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

April 08, 2003

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 10/252,040

FILING DATE: September 23, 2002

**PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)**



**By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS**

P. Swain

**P. SWAIN
Certifying Officer**

BEST AVAILABLE COPY

ORDER NUMBER	991152
REFERENCE ORDER NUMBER	0
BIN NUMBER	0

Page 1 of 1



DELIVERY INSTRUCTIONS

ORDER DATE/TIME	PALM NUMBER	CUSTOMER NUMBER	CONTACT PHONE NUMBER	PAYMENT METHOD	TOTAL COST OF ORDER
2003/04/07 08:30:00		IDON342112		DEPOSIT ACCOUNT	\$ 20.00

BROADCAST MESSAGE

Please provide a copy of this packing slip to your accounting department to assist in reconciling your PTO de account records.


ORDER INFORMATION

ORDER LINE	PRODUCT TYPE	DOCUMENT IDENTIFIER	COPIES	STATUS	CUSTOMER REFERENCE
1	B1	10252040	1	FILLED	25083(26014)

26014

23 Sept 2003

E-MAIL
FAX NUMBER
CARRIER
CARRIER TRACKING NUMBER
CARRIER ACCOUNT NUMBER



DIRECTOR OF PATENTS AND TRADEMARKS
WASHINGTON D.C. 20231

Case Docket No. 25083

Sir:

Transmitted herewith for filing is the Patent Application of:

Inventor : Yuval OVADIA

FOR : INSPECTION SYSTEM FOR LIMITED ACCESS SPACES


Enclosed are:

- ☒ 6 sheets of drawings
- ☒ Assignment to: S.T.I. Security Technology Integration Ltd.
- ☒ Applicant is entitled to Small Entity Status under 37 CFR 1.9 and 37 CFR 1.27
- ☐ Sequence Listing Statement: The sequence listing information recorded in computer readable form is identical to the written (on paper or compact disc) sequence listing
- ☐ Priority Document of _____

THE FILING FEE HAS BEEN CALCULATED AS SHOWN BELOW:

FOR:	Column 1 No. FILED	Column 2 No. EXTRA	SMALL ENTITY		OTHER THAN A SMALL ENTITY	
			RATE	FEE	RATE	FEE
Basic Fee				\$ 370		\$ 740
Total Claims	23 - 20=	3	3 x \$ 9	\$ 27	x \$ 18	\$
Independent Claims	3 - 3=		x x \$ 42	\$	x \$ 84	\$
			\$ 40	\$ 40	+\$ 40	\$
<input checked="" type="checkbox"/> Record of Assignment \$40						
(If the difference in Column 1 is less than "0", enter "0" in Col. 2)			TOTAL	\$ 437	TOTAL	\$

- ☒ Please charge my deposit account No. 50-1407 in the amount of \$437.
 A duplicate copy of this sheet is enclosed.
- ☒ The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No 50-1407. A duplicate copy of this sheet is enclosed.
- ☒ Any additional filing fees required under 37 CFR 1.16.
- ☒ Any patent application processing fees under 37 CFR 1.17.
- ☒ The Commissioner is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to deposit Account No. 50-1407. A duplicate copy of this sheet is enclosed.
- ☒ Any patent application processing fees under 37 CFR 1.17
- ☒ Any filing fees under 37 CFR 1.16 for presentation of extra claims.

Respectfully,

 Shmuel Shelnberg
 Registration No. 25,457

Ramat Gan, Israel
 23 September 2002

09/23/02
 10923 U.S. PTO

11036 U.S. PTO
 10/25/2040
 09/23/02

APPLICATION FOR PATENT

5

Inventor(s): Yuval Ovadia

10

Title: INSPECTION SYSTEM FOR LIMITED ACCESS SPACES

FIELD AND BACKGROUND OF THE INVENTION

The present invention relates to an inspection system for limited access spaces and, more particularly, but not exclusively to a vehicle inspection system suitable for inspection of parts of vehicles that are awkward to inspect easily.

Vehicle underside inspection is necessary for several reasons, one being to provide security, a second being for safety and a third being for contraband detection, by customs inspectors and the like. On the security side, undersides of vehicles may have concealed explosive devices. Of particular concern is the possibility of concealing an explosive device on the underside of a fuel tanker, which device is timed or controlled to explode when the tanker is inside a fuel distribution depot. Carrying out detailed manual inspections of the undersides of each tanker entering a fuel depot is both time and labor consuming. On the safety side, the underside of the vehicle may conceal a mechanical flaw, the early detection of which may prevent an accident. In a garage or workshop a car is generally jacked up or placed on a ramp. Larger vehicles are placed on ramps or are driven over inspection pits. However, outside the garage environment, inspection of the underside of a vehicle is difficult. Contraband detection at borders by customs officials is often based on spot checks since customs very rarely have the resources to inspect every passing vehicle. Any means of allowing a more detailed inspection in a smaller time frame would be welcome.

Security checks for entry into government buildings and the like are typically carried out using a mirror on the end of a pole, which is inserted under the vehicle. However, without illumination it is difficult to see much detail and even with illumination, an explosive device can be concealed in a spot that is awkward to view using the mirror. Furthermore such a mirror is very unlikely to spot hairline cracks.

which are usually the first signs of dangerous mechanical faults. It is impractical to install inspection pits at all places where regular vehicle checks are desirable.

US Patent No. US6249567 to Rothschild et al discloses an inspection system for inspecting a vehicle moving at a grade of travel over a surface and for detecting material disposed within or on the underside of the vehicle. The system has a source for providing a generally upward or downward pointing beam of penetrating radiation of specified cross-section so as to illuminate vehicles driven above or below the source of radiation. A detector arrangement, disposed below the grade of travel, detects radiation from the beam scattered by any material disposed on the underside of the moving vehicle and generates a scattered radiation signal that may be used for characterizing the material disposed on the underside of the vehicle. Similarly, a detector arrangement disposed above the vehicle generates a scattered radiation signal that may be used for characterizing the material disposed within the vehicle. The system however sits at a single location, requiring the vehicle to move during inspection. It cannot independently scan the vehicle underside. Furthermore, the main detection function of the system is based on x-rays, since a principle intention is to scan for the internal contents of the vehicle.

There is thus a widely recognized need for, and it would be highly advantageous to have, a vehicle inspection system devoid of the above limitations.

SUMMARY OF THE INVENTION

According to one aspect of the present invention there is provided a limited access space inspection system comprising:

an imaging device for imaging a region in said limited access space,
a mounting for mounting said imaging device to be scannable about said limited access space and

a scanning control unit, associated with said imaging device, for controlling said imaging device to scan about said limited access space.

The system preferably comprises a protective housing for protecting said imaging device from the environment by interposing between at least said imaging device and said region to be imaged.

Preferably, said protective housing comprises a transparent region located between said imaging device and said region to be imaged.

Preferably, said transparent region comprises laminated glass.

Preferably, said laminated glass is triplex laminated glass.

Preferably, said mounting is a floor mounting for mounting said imaging device at floor level.

Preferably, said mounting comprises a camera track for movably bearing said imaging device.

Preferably, said mounting comprises guide tracks for guiding a vehicle thereover, an underside of said vehicle thereby forming said limited access space.

Preferably, said mounting is a flush floor mounting for insertion into a floor cavity.

The system preferably comprises an illumination source for providing illumination to said limited access space.

The system preferably comprises a display output for providing a display signal.

Preferably, an image processor is located between said imaging device and said display output to process images from said imaging device prior to output.

Preferably, said image processor is operable to compare a current image of said region with a previous image to detect differences therebetween.

Preferably, said imaging device is linearly movable along said camera track, is rotatable about an axis perpendicular to said track, and is further rotatable about an axis parallel to said track.

Preferably, said scanning control unit is controllable by at least one of direct user input and by preprogramming, to scan said imaging device about said limited access space.

According to a second aspect of the present invention there is provided a vehicle underside inspection system comprising:

a floor mounted track,

an imaging device mounted on said floor track to be linearly movable along said floor track, and

a display output, associated with said imaging device, for providing a display signal of output of said imaging device.

The system preferably comprises a scanning controller for controlling said imaging device to scan an imaging region over said floor track.

4

Preferably, said imaging device is rotatable about an axis perpendicular to said floor track, and is further rotatable about an axis parallel to said floor track.

Preferably, said floor mounted track comprises an outer housing and wherein said imaging device is sealed within said outer housing.

According to a third aspect of the present invention there is provided a method of scanning a limited access space, the method comprising:
interpolating a linear track into said space, said linear track having an imaging device movably mounted thereon, and
moving said imaging device along said track, thereby to scan said space.

Preferably, said interpolating said linear track into said space comprises locating a vehicle over said track, an underside of said vehicle forming said limited access space.

The method preferably further comprises interpolating an illumination source into said space.

Preferably, said linear track is flush with a floor.

Unless otherwise defined, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. The materials, methods, and examples provided herein are illustrative only and not intended to be limiting.

- 5 Implementation of the method and system of the present invention involves performing or completing certain selected tasks or steps such as scanning manually, automatically, or a combination thereof. Moreover, according to actual instrumentation and equipment of preferred embodiments of the method and system of the present invention, several selected steps could be implemented by hardware or by
10 software on any operating system of any firmware or a combination thereof. For example, as hardware, selected steps of the invention could be implemented as a chip or a circuit. As software, selected steps of the invention could be implemented as a plurality of software instructions being executed by a computer using any suitable operating system. In any case, selected steps of the method and system of the
15 invention could be described as being performed by a data processor, such as a computing platform for executing a plurality of instructions.

BRIEF DESCRIPTION OF THE DRAWINGS

5

The invention is herein described, by way of example only, with reference to the accompanying drawings. With specific reference now to the drawings in detail, it is stressed that the particulars shown are by way of example and for purposes of illustrative discussion of the preferred embodiments of the present invention only, and are presented in the cause of providing what is believed to be the most useful and readily understood description of the principles and conceptual aspects of the invention. In this regard, no attempt is made to show structural details of the invention in more detail than is necessary for a fundamental understanding of the invention, the description taken with the drawings making apparent to those skilled in the art how the several forms of the invention may be embodied in practice.

In the drawings:

FIG. 1 is a simplified diagram showing a vehicle underside inspection system according to a first preferred embodiment of the present invention;

FIG. 2 is a simplified block diagram showing electronic subsystems of the vehicle underside inspection system of Fig. 1;

FIG. 3 is a simplified cross section of the vehicle underside inspection system of Fig. 1;

Fig. 4 is a flow chart showing a first embodiment of operation of the system of Fig. 1;

Fig. 5 is a flow chart showing a second embodiment of operation of the system of Fig. 1,

Fig. 6 is a schematic diagram showing assembly details of a prototype embodiment of the present invention viewed from the side, and

Fig. 7 is a schematic diagram showing assembly details of the same prototype as viewed along the direction of the track.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present embodiments comprise a controllably movable imaging device mounted on a camera track. The track may be floor mounted to allow vehicles to be driven over it and may further include an illumination source. The imaging device, preferably a still or video camera, may be scanned along a vehicle underside as an operator views the resulting images on a screen. The imaging device is preferably

6

sealed under laminated glass to protect from environmental hazards. The camera track may be mounted between vehicle guide tracks.

The principles and operation of a controllably movable imaging device mounted on a camera track according to the present invention may be better understood with reference to the drawings and accompanying description.

Before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments or of being practiced or carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein is for the purpose of description and should not be regarded as limiting.

Referring now to the drawings, Figure 1 illustrates a limited access space inspection system. The inspection system 10 comprises an imaging device 12 for imaging a region in the limited access space. The imaging device 12 is mounted on a track 14 within a track mounting 16. The imaging device 12 is linearly movable along the track 14 in the direction of arrow 18 and is preferably also able to rotate about the track and about an axis perpendicular to the track, the latter at 360°, with the help of controllable actuators. In a preferred embodiment the imaging device is a dome-mounted camera system, such as the Sivil Mini Dome System 3 marketed by Siemens GmbH of Munich, Germany. Such a dome system automatically provides numerous camera movement features such as rotation, tilt, pan, zoom-in, zoom-out and the like and is fully programmable.

The camera is preferably a standard black and white or color still or video camera. In a preferred embodiment the camera is able to alternate between black and white and color modes. Alternatively, depending on what the system is being used to monitor, infra-red or x-ray or other radiation detectors may be used.

The track mounting 16 is preferably located between vehicle guide tracks 20, to allow a vehicle to position itself above the imaging device 12. The track mounting is preferably designed to be inserted into the floor so that a vehicle simply has to drive onto the vehicle guide tracks to provide the imaging device with a clear view of the underside of the vehicle.

Reference is now made to Fig. 2, which is a simplified block diagram showing the various electronic subsystems of the inspection system of Fig. 1. An imaging subsystem 22 comprises a camera or other imaging device and associated imaging electronics. A scanning subsystem 24 comprises a scanning control subsystem 26 and an actuation subsystem 28. The actuation subsystem moves the camera through linear and rotary motion in accordance with instructions from the scanning control subsystem. The scanning control subsystem controls the camera to scan the vehicle underside, either according to a pre-recorded program or according to instructions received from the user or operator as he views the output on a screen.

10 An image processing subsystem 30 carries out various image-processing operations additional to those that a typical camera may normally provide. For example it may increase contrasts, use an overall lighting level to select between color and black and white modes, and in a particularly preferred embodiment may carry out alignment between a current image and a stored image and then carry out a comparison in order to detect differences between the two images. Such a comparison is useful for mechanical inspections of the same vehicle. That is to say an inspection of a given vehicle may be compared with an earlier inspection of the same vehicle so as to detect the appearance of cracks or the development of existing cracks. In automated security comparison may be made with a stored image of the same type of vehicle so as to highlight obvious differences such as the insertion of an explosive device.

20 A viewing subsystem 32 takes output either directly from the imaging subsystem 22 or from the image processing subsystem 30 and displays it. The viewing subsystem 22 may use any kind of visual display unit. An illumination subsystem 34 preferably comprises a light or other illumination source, which preferably moves along with the imaging device 12. If a radiation detector for radiation other than light is used then the illumination source is selected accordingly.

Reference is now made to Fig. 3, which is a simplified cross-section of the track mounting 16 of Fig. 1. Track mounting 16 comprises a base 40 upon which is mounted camera track 14. Camera track 14 may be toothed along its length to improve traction and accuracy of the actuation system. The imaging device 12 is preferably mounted within a dome construction 42, as described above. Track mounting 16 further comprises a protective housing 44 for protecting the imaging

device from the environment. The protective housing preferably seals the imaging device and supporting electronics from the external environment. At the very least the protective housing interposes between the imaging device and the region to be imaged, thus protecting the imaging device from oil spillage, knocks and other hazards.

Preferably, the protective housing comprises a transparent region located between the imaging device and the region to be imaged. In an embodiment, the transparent region comprises laminated glass, and in a prototype triplex laminated glass of 22mm thickness was used.

Preferably, the mounting is a floor mounting for mounting the imaging device at floor level. In a particularly preferred embodiment, the mounting is a flush floor mounting for insertion into a floor cavity.

Reference is now made to Fig. 4, which is a simplified flow chart showing operation of a preferred embodiment of the present invention. In Fig. 4 a vehicle is driven onto a rail carrying an imaging device. The invention is not however restricted to "drive-on" inspection of vehicles and thus, as an alternative, it is possible to insert a rail carrying an imaging assembly into any kind of space that it is difficult to access and then to operate the assembly to scan the space. In either case, the imaging device then scans the space, either under control of a program or according to instructions from an operator. The output is viewed and the operator decides whether any kind of action is necessary. The output may additionally be recorded if desired.

Reference is now made to Fig. 5, which is a flow chart showing operation according to an alternative embodiment of the present invention. Stages that are identical to those of Fig. 4 are not described again except as necessary for an understanding of the present embodiment. In Fig. 5 the positioning and scanning stages are the same. However at that point a previous scan of the same vehicle or same kind of vehicle is retrieved if available and a comparison is carried out between the two scans. The operator is then alerted regarding any differences.

Reference is now made to Fig. 6, which is a simplified schematic diagram showing assembly details of a prototype embodiment of part of an inspection system according to the present invention viewed from the side. Reference is simultaneously made to Fig. 7 which shows the same assembly viewed along the direction of the rail. Parts that are the same as in previous figures are given the same reference numerals and are not described again except to the extent necessary for an understanding of the

9

present figure. The dome construction 42 is located on track 14 which itself is located on track mounting 16. A motor 50 is provided alongside the dome construction 42 to provide the dome construction with traction to run along the track 14. The motor 50 powers toothed pulleys 52, which intermesh with a toothed central runway of the track 14, thereby to provide the traction.

It is expected that during the life of this patent many relevant imaging devices and systems will be developed and the scope of the terms herein, particularly of the terms "camera" and "imaging system", is intended to include all such new technologies *a priori*.

5 Additional objects, advantages, and novel features of the present invention will become apparent to one ordinarily skilled in the art upon examination of the following examples, which are not intended to be limiting. Additionally, each of the various embodiments and aspects of the present invention as delineated hereinabove and as claimed in the claims section below finds experimental support in the following
10 examples.

It is appreciated that certain features of the invention, which are, for clarity, described in the context of separate embodiments, may also be provided in combination in a single embodiment. Conversely, various features of the invention, which are, for brevity, described in the context of a single embodiment, may also be
15 provided separately or in any suitable subcombination.

Although the invention has been described in conjunction with specific embodiments thereof, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art. Accordingly, it is intended to embrace all such alternatives, modifications and variations that fall within the spirit and broad
20 scope of the appended claims. All publications, patents and patent applications mentioned in this specification are herein incorporated in their entirety by reference into the specification, to the same extent as if each individual publication, patent or patent application was specifically and individually indicated to be incorporated herein by reference. In addition, citation or identification of any reference in this application
25 shall not be construed as an admission that such reference is available as prior art to the present invention.

WHAT IS CLAIMED IS:

1. A limited access space inspection system comprising:
an imaging device for imaging a region in said limited access space,
a mounting for mounting said imaging device to be scannable about said limited access space and
a scanning control unit, associated with said imaging device, for controlling said imaging device to scan about said limited access space.
2. The system of claim 1, further comprising a protective housing for protecting said imaging device from the environment by interposing between at least said imaging device and said region to be imaged.
3. The system of claim 1, wherein said protective housing comprises a transparent region located between said imaging device and said region to be imaged.
4. The system of claim 3, wherein said transparent region comprises laminated glass.
5. The system of claim 4, wherein said laminated glass is triplex laminated glass.
6. The system of claim 1, wherein said mounting is a floor mounting for mounting said imaging device at floor level.
7. The system of claim 1, wherein said mounting comprises a camera track for movably bearing said imaging device.
8. The system of claim 1, wherein said mounting comprises guide tracks for guiding a vehicle thereover, an underside of said vehicle thereby forming said limited access space.

11

9. The system of claim 6, wherein said mounting is a flush floor mounting for insertion into a floor cavity.

10. The system of claim 1, further comprising an illumination source for providing illumination to said limited access space.

11. The system of claim 1, further comprising a display output for providing a display signal.

12. The system of claim 11, further comprising an image processor, located between said imaging device and said display output to process images from said imaging device prior to output.

13. The system of claim 12, wherein said image processor is operable to compare a current image of said region with a previous image to detect differences therebetween.

14. The system of claim 7, wherein said imaging device is linearly movable along said camera track, is rotatable about an axis perpendicular to said track, and is further rotatable about an axis parallel to said track.

15. The system of claim 14, wherein said scanning control unit is controllable by at least one of direct user input and by preprogramming, to scan said imaging device about said limited access space.

16. A vehicle underside inspection system comprising:
a floor mounted track,
an imaging device mounted on said floor track to be linearly movable along said floor track, and
a display output, associated with said imaging device, for providing a display signal of output of said imaging device.

12

17. The system of claim 16, further comprising a scanning controller for controlling said imaging device to scan an imaging region over said floor track.

18. The system of claim 17, wherein said imaging device is rotatable about an axis perpendicular to said floor track, and is further rotatable about an axis parallel to said floor track.

19. The system of claim 16, wherein said floor mounted track comprises an outer housing and wherein said imaging device is sealed within said outer housing.

20. A method of scanning a limited access space, the method comprising: interpolating a linear track into said space, said linear track having an imaging device movably mounted thereon, and moving said imaging device along said track, thereby to scan said space.

21. The method of claim 20, wherein said interpolating said linear track into said space comprises locating a vehicle over said track, an underside of said vehicle forming said limited access space.

22. The method of claim 20, further comprising interpolating an illumination source into said space.

23. The method of claim 21, wherein said linear track is flush with a floor.

13

ABSTRACT OF THE DISCLOSURE

A limited access space inspection system comprising: an imaging device for imaging a region in the limited access space, a mounting for mounting the imaging device to scan about the limited access space and a scanning control unit, associated with the imaging device, for controlling the imaging device to scan about the limited access space. The device is particularly useful for improving by automation, security checks, customs checks and safety checks involving such awkward to access spaces.

Express Mail Label No.

Docket No.
25083**Declaration and Power of Attorney For Patent Application****English Language Declaration**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

INSPECTION SYSTEM FOR LIMITED ACCESS SPACES

the specification of which

☒ is attached hereto.☐ was filed on _____ as United States Application No. or PCT

International Application Number _____

and was amended on _____

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d) or Section 365(b) of any foreign application(s) for patent or inventor's certificate, or Section 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

Priority Not Claimed

(Number)

(Country)

(Day/Month/Year Filed)



(Number)

(Country)

(Day/Month/Year Filed)



(Number)

(Country)

(Day/Month/Year Filed)



I hereby claim the benefit under 35 U.S.C. Section 119(e) of any United States provisional application(s) listed below:

(Application Serial No.)

(Filing Date)

(Application Serial No.)

(Filing Date)

(Application Serial No.)

(Filing Date)

I hereby claim the benefit under 35 U.S.C. Section 120 of any United States application(s), or Section 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. Section 112. I acknowledge the duty to disclose to the United States Patent and Trademark Office all the information known to me to be material to patentability as defined in Title 37, C.F.R., Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

(Application Serial No.)

(Filing Date)

(Status)
(patented, pending, abandoned)

(Application Serial No.)

(Filing Date)

(Status)
(patented, pending, abandoned)

(Application Serial No.)

(Filing Date)

(Status)
(patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

23/09 02 MON 16:28 FAX 972 3 8127575
FROM : METAL I.R. CHURI L.T.D.

G. E. EHRLICH
PHONE NO. : 972 9 917476

0022
1025350001:44PM 9/23/02

23/09 02 MON 16:04 FAX 972 3 8127575

G. E. EHRLICH

0005

Page 3 of 3

25083

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. *(list name and registration number)*


Sol SHEINBEIN,	Registration Number 25,457
D'vorah GRAESER,	Registration Number 40,000
Martin MOYNIHAN	Registration Number 40,338
Rachel ABOUDI,	Registration Number 44,490

Send Correspondence to: G.E. EHRLICH (1995) LTD,
c/o ANTHONY CASTORINA
2001 JEFFERSON DAVIS HIGHWAY, SUITE 207
ARLINGTON, VIRGINIA 22202

Direct Telephone Calls to: *(name and telephone number)*

Anthony Castorina Tel. No. (703) 415-1581
Fax No. (703) 415-4864

FULL NAME OF SOLE OR FIRST INVENTOR		YUVAL OVADIA
Sole or first inventor's signature		Date 23.9.2002
Residence	: Kibbutz Yagur, 30065 Israel	
Citizenship	: Israeli	
Post Office Address	: Kibbutz Yagur, 30065 Israel	







Fig. 2






Fig. 4






Fig. 5



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.